

GBU Plastic-Encapsulate Bridge Rectifier

Features


- I_O 4.0A
- V_{RRM} 50V-1000V
- High surge current capability
- Polarity: Color band denotes cathode

Applications

- General purpose 1 phase Bridge rectifier applications

Marking

- GBU4XX
- XX : From 005 To 10



Limiting Values (Absolute Maximum Rating)

Item	Symbol	Unit	Conditions		GBU4						
					005	01	02	04	06	08	10
Repetitive Peak Reverse Voltage	V _{RRM}	V			50	100	200	400	600	800	1000
Average Rectified Output Current	I _O	A	60Hz sine wave, R-load	With heatsink T _c =100℃	4						
				Without heatsink T _a =100℃	2.4						
Surge(Non-repetitive)Forward Current	I _{FSM}	A	60Hz sine wave, 1 cycle, T _j =25℃		150						
Current Squared Time	I ² t	A ² S	1ms≤t<8.3ms T _j =25℃， Rating of per diode		93						
Storage Temperature	T _{stg}	℃			-55 ~+150						
Junction Temperature	T _j	℃			-55 ~+150						
Dielectric Strength	V _{dis}	KV	Terminals to case AC 1 minute		2						
Mounting Torque	Tor	kg • cm	Recommend torque: 5kg • cm		8						

Electrical Characteristics ($T_a = 25^\circ\text{C}$ Unless otherwise specified)

Item	Symbol	Unit	Test Condition	Max
Peak Forward Voltage	V_{FM}	V	$I_{FM} = 2\text{A}$, Pulse measurement, Rating of per diode	1.0
Peak Reverse Current	I_{RRM}	μA	$V_{RM} = V_{RRM}$, Pulse measurement, Rating of per diode	10
Thermal Resistance	$R_{\theta J-A}$	$^\circ\text{C}/\text{W}$	Between junction and ambient Without heatsink	23
	$R_{\theta J-C}$		Between junction and case, With heatsink	5.5

Typical Characteristics

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL JUNCTION CAPACITANCE




FIG.4-TYPICAL FORWARD CHARACTERISTICS






FIG.5-TYPICAL REVERSE CHARACTERISTICS



The curve graph is for reference only, can't be the basis for judgment(曲线图仅供参考)!

GBU Package Outline Dimensions



Unit: in inches (millimeters)

NOTICE

JSMD reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSMD does not assume any liability arising out of the application or use of any product described herein.