

Integrated bypass diode for Solar cell Module

MAIN CHARACTERISTICS


I_O	30 A
V_{RRM}	45 V
T_j	200 °C
$V_{F(typ)}$	0.51V

FEATURES

- Schottky Barrier high diode;
- Low thermal resistance;
- Lower forward voltage drop, low power loss;
- Isolate Package design, ideal for heat dispersion;
- High forward current capability;
- Excellent anti-humidity;
- Low profile package;
- High forward surge capability;

Mechical Data

- Case: 09E;
- Terminals: Copper;
- High temperature soldering guaranteed;
Heated-tool welding 260°C, 10seconds
- Marking: As marked on product;



MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)





Symbol	Parameter	GP3045	Unit
V_{RRM}	Peak repetitive reverse voltage	45	V
V_{RWM}	Working peak reverse voltage		
V_R	DC blocking voltage		
$V_{R(RMS)}$	RMS reverse voltage	31.5	V
I_O	Average rectified output current@60Hz half sine-wave, R-load, $T_a=25^{\circ}\text{C}$	30	A
I_{FSM}	Non-Repetitive peak forward surge current (8.3ms half sine wave)	400	A
I^2t	Rating for fusing ($t<8.3\text{ms}$)	664	A^2S
$R_{\theta jc}$	Thermal resistance from junction to case	1.5	$^{\circ}\text{C}/\text{W}$
T_j	Junction temperature IN DC Forward Mode-Forward Operations, without reverse bias, $t \leq 1\text{ h}$ (1)	-55~+200	$^{\circ}\text{C}$
T_{stg}	Storage temperature	-55~+150	$^{\circ}\text{C}$


NOTE: (1) Meets the requirements of IEC 61215 Ed. 2 bypass diode thermal test.

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse voltage	$V_{(BR)}$	$I_R=1\text{mA}$	45			V
Reverse current	I_R	$V_R=45\text{V}$	$T_j=25^{\circ}\text{C}$	50	100	μA
			$T_j=100^{\circ}\text{C}$		10	mA
Forward voltage	V_F	$I_F=30\text{A}$	$T_j=25^{\circ}\text{C}$	0.51	0.55	V

Typical Characteristics





Symbol	Dinemsions In Millimeters		Dinemsions In Inches	
	Min	Max	Min	Max
A	7.800	8.200	0.307	0.323
B	11.350	11.750	0.447	0.463
C	22.500	23.500	0.886	0.925
D	26.500	27.500	1.043	1.083
E	10.500	11.500	0.413	0.453
F	14.500	15.500	0.571	0.610
G	16.500	17.500	0.650	0.689
H	31.500	32.500	1.240	1.280
I	41.500	42.500	1.634	1.673
J	5.700	6.300	0.224	0.248
K	5.750	6.150	0.226	0.242
L	1.700	2.100	0.067	0.083
M	1.700	2.100	0.067	0.083
N	4.300	4.700	0.169	0.185
O	0.600	0.800	0.024	0.031
P	0.800 TYP		0.031 TYP	
Q	1.000 TYP		0.039 TYP	
R	1.250 TYP		0.049 TYP	

Ordering Information

PREFERED P/N	TUBE(pcs)	CARTON(pcs)
GP3045	30	1500

Disclaimer

The information presented in this document is for reference only. JIANGSU High Diode Semiconductor Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), High Diode or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.h-diode.com](http://www.h-diode.com) , or consult your nearest HighDiode's sales office for further assistance.