

SOT-23 Plastic-Encapsulate MOSFET

12V P-Channel MOSFET

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
-12V	30mΩ@-4.5V	-4.1A
	40mΩ@-2.5V	
	60mΩ@-1.8V	

Feature

TrenchFET Power MOSFET

Excellent $R_{DS(on)}$ and Low Gate Charge


Application

DC/DC Converter


Load Switch for Portable Devices

Battery Switch

MARKING:




SOT-23



1. GATE
2. SOURCE
3. DRAIN

Schematic diagram



ABSOLUTE MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-12	V
Gate-Source Voltage	V_{GS}	± 10	V
Continuous Drain Current	I_D	-4.1	A
Pulsed Drain Current ($t=300\mu\text{s}$)	I_{DM}	-15	A
Power Dissipation	P_D	0.35	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	357	$^{\circ}\text{C/W}$
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55~ +150	$^{\circ}\text{C}$

Electrical Characteristics (T_A=25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	-12			V
Zero gate voltage drain current	I _{DSS}	V _{DS} = -12V, V _{GS} = 0V			-1	μA
Gate-body leakage current	I _{GSS}	V _{GS} = ± 10V, V _{DS} = 0V			±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	-0.5	-0.65	-0.9	V
Drain-source on-resistance ^a	R _{DS(on)}	V _{GS} = -4.5V, I _D = -3.5A		30	45	mΩ
		V _{GS} = -2.5V, I _D = -3.0A		40	60	
		V _{GS} = -1.8V, I _D = -2.0A		60	90	
Forward tranconductance ^a	g _{FS}	V _{DS} = -5V, I _D = -4.1A	6			S
Dynamic characteristics ^{b,c}						
Input Capacitance	C _{iss}	V _{DS} = -4V, V _{GS} = 0V, f = 1MHz		740		pF
Output Capacitance	C _{oss}			290		
Reverse Transfer Capacitance	C _{rss}			190		
Gate resistance	R _g	f = 1MHz	1.4		14	Ω
Total Gate Charge	Q _g	V _{DS} = -4V, V _{GS} = -2.5V, I _D = -4.1A		4.5	9	nC
Gate-Source Charge	Q _{gs}			1.2		
Gate-Drain Charge	Q _{gd}			1.6		
Turn-on delay time	t _{d(on)}	V _{DD} = -4V, V _{GEN} = -4.5V, I _D = -3.3A R _L = 1.2Ω, R _{GEN} = 1Ω		13	20	ns
Turn-on rise time	t _r			35	53	
Turn-off delay time	t _{d(off)}			32	48	
Turn-off fall time	t _f			10	20	
Turn-on delay time	t _{d(on)}	V _{DD} = -4V, V _{GEN} = -8V, I _D = -3.3A R _L = 6Ω, R _{GEN} = 1Ω		5	10	
Turn-on rise time	t _r			11	17	
Turn-off delay time	t _{d(off)}			22	33	
Turn-off fall time	t _f			16	24	
Source-Drain Diode characteristics						
Diode forward current	I _S	T _C = 25℃			-1.4	A
Diode pulsed forward current ^a	I _{SM}				-10	A
Diode Forward voltage	V _{DS}	V _{GS} = 0V, I _S = -3.3A			-1.2	V







Note :

a. Pulse Test ; Pulse Width ≤300μs, Duty Cycle ≤2%.


b. Guaranteed by design, not subject to production testing.

c. These parameters have no way to verify.

Typical Characteristics




SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Note:


1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JSJD reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSJD does not assume any liability arising out of the application or use of any product described herein.

Reel Taping Specifications For Surface Mount Devices-SOT-23

SOT-23 Embossed Carrier Tape




Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×230	