

GBP Plastic-Encapsulate Bridge Rectifier

Features


- I_O 2.0A
- V_{RRM} 50V-1000V
- High surge current capability

Applications

- General purpose 1 phase Bridge rectifier applications

Marking

- GBP2XX
- XX : From 005 To 10



Limiting Values (Absolute Maximum Rating)

Item	Symbol	Unit	Conditions		GBP2						
					005	01	02	04	06	08	10
Repetitive Peak Reverse Voltage	V _{RRM}	V			50	100	200	400	600	800	1000
Average Rectified Output Current	I _O	A	60Hz sine wave, R-load	Tc=100℃	2.0						
Surge(Non-repetitive)Forward Current	I _{FSM}	A	60Hz sine wave, 1 cycle, T _j =25℃		60						
Current Squared Time	I ² t	A ² S	1ms≤t<8.3ms T _j =25℃， Rating of per diode		15						
Storage Temperature	T _{stg}	℃			-55 ~+150						
Junction Temperature	T _j	℃			-55 ~+150						

Electrical Characteristics ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

Item	Symbol	Unit	Test Condition	Max
Peak Forward Voltage	V_{FM}	V	$I_{FM}=2.0\text{A}$, Pulse measurement, Rating of per diode	1.1
Peak Reverse Current	I_{RRM}	μA	$V_{RM}=V_{RRM}$, Pulse measurement, Rating of per diode	10
Thermal Resistance	$R_{\theta J-A}$	$^{\circ}\text{C/W}$	Between junction and ambient	47
	$R_{\theta J-C}$		Between junction and lead	10

Typical Characteristics

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL JUNCTION CAPACITANCE




FIG.4-TYPICAL FORWARD CHARACTERISTICS






FIG.5-TYPICAL REVERSE CHARACTERISTICS



The cruve graph is for reference only, can't be the basis for judgment

GBP Package Outline Dimensions



NOTICE

JSHD reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSHD does not assume any liability arising out of the application or use of any product described herein.