

SOT-23 Plastic-Encapsulate MOSFET

50V P-Channel MOSFET

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
-50V	1.7Ω@-10V	-0.13A
	1.9Ω@-4.5V	


Feature

- Trench Technology MOSFET
- Low Gate Charge

Application

- Load Switch for Portable Devices
- DC/DC Converter

MARKING:



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain - Source Voltage	V_{DS}	-50	V
Gate - Source Voltage	V_{GS}	±20	V
Continuous Drain Current ¹	I_D	-0.13	A
Pulsed Drain Current ²	I_{DM}	-1.2	A
Power Dissipation ⁴	P_D	300	mW
Thermal Resistance from Junction to Ambient ⁵	$R_{\theta JA}$	417	°C/W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STG}	-55~ +150	°C







Electrical Characteristics (T_A=25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain – Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	-50			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -50V, V _{GS} = 0V			-1	μA
Gate – Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
On Characteristics ³						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	-0.9	-1.4	-2.0	V
Drain-source On-resistance	R _{DS(on)}	V _{GS} = -10V, I _D = -0.1A		1.7	5	Ω
		V _{GS} = -4.5V, I _D = -0.1A		1.9	6	
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} = -25V, V _{GS} = 0V, f = 1MHz		32.9		pF
Output Capacitance	C _{oss}			5.48		
Reverse Transfer Capacitance	C _{rss}			3.31		
Gate Resistance	R _g	V _{DS} = 0V, V _{GS} = 0V, f = 1MHz		73		Ω
Switching Characteristics						
Total Gate Charge	Q _g	V _{DS} = -10V, V _{GS} = -10V, I _D = -0.1A		0.62		nC
Gate-source Charge	Q _{gs}			0.13		
Gate-drain Charge	Q _{gd}			0.11		
Turn-on Delay Time	t _{d(on)}	V _{DD} = -30V, V _{GS} = -10V, R _L = 110Ω, R _G = 50Ω		11		ns
Turn-on Rise Time	t _r			6		
Turn-off Delay Ttime	t _{d(off)}			19		
Turn-off Fall Ttime	t _f			8		
Source - Drain Diode Characteristics						
Diode Forward Voltage ³	V _{SD}	V _{GS} = 0V, I _S = -0.1A			-1.2	V


Notes :

- 1.The maximum current rating is limited by Chip.
- 2.Pulse Test : Pulse Width ≤ 10μs, duty cycle ≤ 1%.
- 3.Pulse Test : Pulse Width ≤ 300μs, duty cycle ≤ 2%.
- 4.The power dissipation P_D is limited by T_{J(MAX)} = 150°C.
- 5.Device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C.

Typical Characteristics




SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0	0.100	0	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.150	1.500	0.045	0.059
E1	2.250	2.650	0.089	0.104
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Note:


1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JSMD reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSMD does not assume any liability arising out of the application or use of any product described herein.

Reel Taping Specifications For Surface Mount Devices-SOT-23


SOT-23 Embossed Carrier Tape




Packaging Description:
SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×230	