

## TO-263-2L Plastic-Encapsulate Diodes

SUPER FAST RECOVER RECTIFIER

### MAIN CHARACTERISTICS

|              |                               |
|--------------|-------------------------------|
| $I_O$        | 20A                           |
| $V_{RRM}$    | 600 V                         |
| $T_j$        | 150 °C                        |
| $V_{F(typ)}$ | 1.17V (@ $T_j=125^{\circ}C$ ) |

### FEATURES



- Ultrafast 35ns Recovery Times
- High Voltage Capability to 600V
- Low Reverse Leakage Current
- Typical applications are in switching power supplies, converters freewheeling diodes, and reverse battery protection.

### Mechical Data

- Case: TO-263-2L (D<sup>2</sup>PAK)
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Solder plated, solderable per MIL- STD-202, Method 208
- Polarity: Color band denotes cathode end

TO-263-2L

1. ANODE
2. CATHODE
3. ANODE



### MAXIMUM RATINGS ( $T_a=25^{\circ}C$ unless otherwise noted )

| Symbol          | Parameter                                                        | Value    | Unit |
|-----------------|------------------------------------------------------------------|----------|------|
| $V_{RRM}$       | Peak repetitive reverse voltage                                  | 600      | V    |
| $V_{RWM}$       | Working peak reverse voltage                                     |          |      |
| $V_R$           | DC blocking voltage                                              |          |      |
| $V_{R(RMS)}$    | RMS reverse voltage                                              | 420      | V    |
| $I_O$           | Average rectified output current                                 | 20       | A    |
| $I_{FSM}$       | Non-Repetitive peak forward surge current (8.3ms half sine wave) | 125      | A    |
| $R_{\theta JC}$ | Thermal resistance from junction to case                         | 2.0      | °C/W |
| $R_{\theta JA}$ | Thermal resistance from junction to ambient                      | 62.5     | °C/W |
| $T_j$           | Junction temperature                                             | 150      | °C   |
| $T_{stg}$       | Storage temperature                                              | -55~+150 | °C   |

### ELECTRICAL CHARACTERISTICS ( $T_a=25^{\circ}C$ unless otherwise specified)

| Parameter                 | Symbol     | Test conditions                  | Min                | Typ  | Max | Unit    |
|---------------------------|------------|----------------------------------|--------------------|------|-----|---------|
| Reverse voltage           | $V_{(BR)}$ | $I_R=100\mu A$                   | 600                |      |     | V       |
| Reverse current           | $I_R$      | $V_R=600V$                       | $T_j=25^{\circ}C$  | 0.1  | 1   | $\mu A$ |
|                           |            |                                  | $T_j=125^{\circ}C$ | 2.0  |     | $\mu A$ |
| Forward voltage           | $V_F$      | $I_F=10A$                        | $T_j=25^{\circ}C$  | 1.4  | 1.6 | V       |
|                           |            |                                  | $T_j=125^{\circ}C$ | 1.17 |     | V       |
| Typical total capacitance | $C_{tot}$  | $V_R=4.0V, f=1MHz$               |                    | 60   |     | pF      |
| Reverse recovery time     | $t_{rr}$   | $I_F=0.5A, I_R=1A, I_{tr}=0.25A$ |                    |      | 35  | ns      |

## Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT




FIG3: Instantaneous Forward Voltage






FIG.4: TYPICAL REVERSE CHARACTERISTICS




## TO-263-2L Package Outline Dimensions



| Symbol | Dimensions In Millimeters |        | Dimensions In Inches |       |
|--------|---------------------------|--------|----------------------|-------|
|        | Min.                      | Max.   | Min.                 | Max.  |
| A      | 4.470                     | 4.670  | 0.176                | 0.184 |
| A1     | 0.000                     | 0.150  | 0.000                | 0.006 |
| B      | 1.120                     | 1.420  | 0.044                | 0.056 |
| b      | 0.710                     | 0.910  | 0.028                | 0.036 |
| b1     | 1.170                     | 1.370  | 0.046                | 0.054 |
| c      | 0.310                     | 0.530  | 0.012                | 0.021 |
| c1     | 1.170                     | 1.370  | 0.046                | 0.054 |
| D      | 10.010                    | 10.310 | 0.394                | 0.406 |
| E      | 8.500                     | 8.900  | 0.335                | 0.350 |
| e      | 2.540 TYP.                |        | 0.100 TYP.           |       |
| e1     | 4.980                     | 5.180  | 0.196                | 0.204 |
| L      | 14.940                    | 15.500 | 0.588                | 0.610 |
| L1     | 4.950                     | 5.450  | 0.195                | 0.215 |
| L2     | 2.340                     | 2.740  | 0.092                | 0.108 |
| L3     | 1.300                     | 1.700  | 0.051                | 0.067 |
| Φ      | 0° 8°                     |        | 0° 8°                |       |
| V      | 5.600 REF.                |        | 0.220 REF.           |       |

## TO-263-2L Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05\text{mm}$ .
3. The pad layout is for reference purposes only.

## Ordering Information

| Part Number | Package   | Shipping Quantity |
|-------------|-----------|-------------------|
| MURB2060CT  | TO-263-2L | 800/tape&Reel     |


## Marking Diagram



XXXX = Code

# TO-263-2L Tape and Reel

## TO-263-2L Embossed Carrier Tape




### Packaging Description:


TO-263-2L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 800 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

| Dimensions are in millimeter |       |       |      |       |      |       |      |       |      |       |
|------------------------------|-------|-------|------|-------|------|-------|------|-------|------|-------|
| Pkg type                     | A     | B     | C    | d     | E    | F     | P0   | P     | P1   | W     |
| TO-263-2L                    | 10.80 | 16.13 | 5.21 | Ø1.55 | 1.75 | 11.50 | 4.00 | 16.00 | 2.00 | 24.00 |

## TO-263-2L Tape Leader and Trailer



## TO-263-2L Reel



| Dimensions are in millimeter |         |        |        |      |      |        |
|------------------------------|---------|--------|--------|------|------|--------|
| Reel Option                  | D       | D1     | D2     | W1   | W2   | I      |
| 13"Dia                       | Ø330.00 | 100.00 | Ø21.00 | 24.4 | 30.4 | Ø13.00 |

| REEL    | Reel Size | Box     | Box Size(mm) | Carton    | Carton Size(mm) | G.W.(kg) |
|---------|-----------|---------|--------------|-----------|-----------------|----------|
| 800 pcs | 13 inch   | 800 pcs | 340×336×36   | 8,000 pcs | 400×353×365     |          |