







SOT-23 Plastic-Encapsulate Transistors


TRANSISTOR(NPN)

Features

- Ideally suited for automatic insertion
- For Switching and AF Amplifier Applications

Marking:

BC846A=1A	BC846B=1B	
		
BC847A=1E	BC847B=1F	BC847C=1G
		
BC848A=1J	BC848B=1K	BC848C=1L
		



Solid dot = Green molding compound device, if none, the normal device.









Limiting Values (Absolute Maximum Rating)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage		V
		BC846	
		BC847	
		BC848	
V_{CEO}	Collector-Emitter Voltage		V
		BC846	
		BC847	
		BC848	
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current –Continuous	0.1	A
P_C	Collector Power Dissipation	200	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	625	°C/W
T_J	Junction Temperature	150	°C
T_{stg}	Storage Temperature	-55~+150	°C


Electrical Characteristics (T_A=25°C unless otherwise noted)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	BC846 BC847 BC848	V _{CBO}	I _C = 10μA, I _E =0	80 50 30		V
Collector-emitter breakdown voltage	BC846 BC847 BC848	V _{CEO}	I _C = 10mA, I _B =0	65 45 30		V
Emitter-base breakdown voltage		V _{EBO}	I _E = 10μA, I _C =0	6		V
Collector cut-off current	BC846 BC847 BC848	I _{CBO}	V _{CB} =70 V , I _E =0 V _{CB} =50 V , I _E =0 V _{CB} =30 V , I _E =0		0.1	μA
Emitter cut-off current		I _{EBO}	V _{EB} =5 V , I _C =0		0.1	μA
DC current gain	BC846A,847A,848A BC846B,847B,848B BC847C,BC848C	h _{FE}	V _{CE} = 5V, I _C = 2mA	110 200 420	220 450 800	
Collector-emitter saturation voltage		V _{CE(sat)}	I _C =100mA, I _B = 5mA		0.5	V
Base-emitter saturation voltage		V _{BE(sat)}	I _C =100mA, I _B = 5mA		1.1	V
Transition frequency		f _T	V _{CE} = 5 V, I _C = 10mA f=100MHz	100		MHz
Collector output capacitance		C _{ob}	V _{CB} =10V,f=1MHz		4.5	pF

Typical Characteristics




SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Note:


1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JSJD reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSJD does not assume any liability arising out of the application or use of any product described herein.

Reel Taping Specifications For Surface Mount Devices-SOT-23

SOT-23 Embossed Carrier Tape




Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×230	