



SOT-23 Plastic-Encapsulate Diodes

Switching Diodes


Features

- Fast Switching Speed
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose Switching Applications
- High Conductance

Marking:

BAS19 : JP	BAS20 : JR
	

Solid dot = Green molding compound device, if none, the normal device.







Limiting Values(Absolute Maximum Rating)

Symbol	Parameter	BAS19	BAS20	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	120	200	V
V_{RWM}	Working Peak Reverse Voltage	100	150	V
I_O	Average Rectified Output Current	200		mA
I_{FSM}	Non-Repetitive Peak Forward Surge Current @t=8.3ms	2.5		A
P_d	Power Dissipation	250		mW
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	500		°C/W
T_J	Junction temperature	150		°C
T_{stg}	Storage Temperature	-55 ~ +150		°C

Electrical Characteristics (Ta=25°C Unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse breakdown voltage	$V_{(BR)}$	$I_R=100\mu A$	120 200			V
Reverse current	I_R	$V_R=100V$ $V_R=150V$			0.1	μA
Forward voltage	V_F	$I_F=100mA$			1	V
		$I_F=200mA$			1.25	V
Diodes capacitance	C_D	$V_R=0V, f=1MHz$			5	pF
Reveres recovery time	t_{rr}	$I_F=I_R=30mA, I_{rr}=0.1*I_R$			50	ns

Typical Characteristics




SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Note:


1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.05 mm.
3. The pad layout is for reference purposes only.

NOTICE

JSJD reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSJD does not assume any liability arising out of the application or use of any product described herein.

Reel Taping Specifications For Surface Mount Devices-SOT-23

SOT-23 Embossed Carrier Tape




Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×230	