

SMCG Plastic-Encapsulate Diodes


Super Fast Recovery Rectifier Diode

Features

- I_o 5A
- VRRM 200V-600V
- Low forward voltage drop
- High surge current capability
- Glass passivated chip junction

Mechical Data

- Case: JEDEC DO-214AB molded plastic
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Solder plated, solderable per MIL-STD-202, Method 208
- Polarity: Color band denotes cathode end



Limiting Values (Absolute Maximum Rating)

| Item | Symbol | Unit | Conditions | MUR | | |
|--------------------------------------|-------------|-------------|---|-----------|------|------|
| | | | | S520 | S540 | S560 |
| Repetitive Peak Reverse Voltage | V_{RRM} | V | | 200 | 400 | 600 |
| Maximum RMS Voltage | V_{RMS} | V | | 140 | 280 | 420 |
| Maximum DC blocking Voltage | V_{DC} | V | | 200 | 400 | 600 |
| Average Forward Current | $I_{F(AV)}$ | A | 60Hz Half-sine wave, Resistance load | 5.0 | | |
| Surge(Non-repetitive)Forward Current | I_{FSM} | A | 60Hz Half-sine wave, 1 cycle, $T_a=25^{\circ}C$ | 125 | | |
| Junction Temperature | T_J | $^{\circ}C$ | | -55~+150 | | |
| Storage Temperature | T_{STG} | $^{\circ}C$ | | - 55~+150 | | |

Electrical Characteristics ($T_a=25^{\circ}C$ Unless otherwise specified)

| Item | Symbol | Unit | Test Condition | MUR | | |
|-----------------------------|------------------|---------------|---------------------------------------|--------------------|------|------|
| | | | | S520 | S540 | S560 |
| Peak Forward Voltage | V_{FM} | V | $I_{FM}=5A$ | 0.93 | 1.30 | |
| Peak Reverse Current | I_{RRM1} | μA | $V_{RM}=V_{RRM}$ | $T_a=25^{\circ}C$ | | |
| | I_{RRM2} | | | $T_a=125^{\circ}C$ | | |
| Reverse Recovery time | t_r | ns | $I_F=0.5A$ $I_R=1A$ $I_{RR}=0.25A$ | 25 | 50 | |
| Thermal Resistance(Typical) | $R_{\theta J-A}$ | $^{\circ}C/W$ | Between junction and ambient | 95 | | |
| | $R_{\theta J-L}$ | | Between junction and lead | 4 | | |

Notes:

Thermal resistance from junction to ambient and from junction to lead mounted on 1" x 1"(25.4mm x 25.4mm) FR4 PCB, double sided copper, with minimum pad layout

Typical Characteristics

FIG1: Io-TL Curve




FIG2: Surge Forward Current Capability




FIG3: Forward Voltage




FIG4: Typical Reverse Characteristics







FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



SMCG Package Outline Dimensions



SMCG Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Ordering Information

| Part Number | Package | Shipping Quantity |
|---------------------|---------|-------------------|
| MURS520- MURS560 | SMCG | 3000/tape&Reel |

Marking Diagram



XX: From 20 To 60

Reel Taping Specifications For Surface Mount Devices-SMCG




FIG : CONFIGURATION OF SURFACE MOUNTED DEVICES TAPING

| ITEM | SYMBOL | SMCG mm(inch) |
|------------------------|--------|------------------------|
| Carrier width | A | 6.05±0.1(0.238±0.004) |
| Carrier length | B | 8.31±0.1(0.327±0.004) |
| Carrier depth | C | 2.70±0.1(0.106±0.004) |
| Sprocket hole | d | 1.55±0.05(0.061±0.002) |
| Reel outside diameter | D | 330±2.0(13±0.079) |
| Reel inner diameter | D1 | 75 ±1.0 (2.95 ±0.039) |
| Feed hole diameter | D2 | 13±0.5(0.512±0.020) |
| Sprocket hole position | E | 1.75±0.1(0.069±0.004) |
| Punch hole position | F | 7.65±0.05(0.301±0.002) |
| Punch hole pitch | P | 8.0±0.1(0.315±0.004) |
| Sprocket hole pitch | P0 | 4.0±0.1(0.157±0.004) |
| Embossment center | P1 | 2.0±0.1(0.079±0.004) |
| Totall tape thickness | T | 0.3±0.1(0.012±0.004) |
| Tape width | W | 16.0±0.2(0.630±0.008) |
| Reel width | W1 | 24.0±2.0(0.945±0.079) |

NOTE:Devices are packde in accordance with EIA standard RS-481-A and specification given above.