


## TO-263-2L Plastic-Encapsulate MOSFETS

80V N-Channel MOSFET

### Features:

- Low Intrinsic Capacitances.
- Excellent Switching Characteristics.
- Extended Safe Operating Area.
- Unrivalled Gate Charge :Qg=60nC (Typ.).
- BV<sub>DSS</sub>=80V, I<sub>D</sub>=100A
- R<sub>DS(on)</sub> : 6.6mΩ (Typ) @V<sub>G</sub>=10V
- 100% Avalanche Tested



### Absolute Maximum Ratings (T<sub>A</sub>=25°C unless otherwise noted)

| Symbol                            | Parameter                            | Maximum               | Unit |
|-----------------------------------|--------------------------------------|-----------------------|------|
| V <sub>DSS</sub>                  | Drain-to-Source Voltage              | 80                    | V    |
| V <sub>GSS</sub>                  | Gate-to-Source Voltage               | ±20                   | V    |
| I <sub>D</sub> <sup>3</sup>       | Continuous Drain Current             | T <sub>C</sub> =25°C  | 100  |
|                                   |                                      | T <sub>C</sub> =100°C | 65   |
| I <sub>DP</sub> <sup>4</sup>      | Pulsed Drain Current                 | T <sub>C</sub> =25°C  | 400  |
| I <sub>AS</sub> <sup>5</sup>      | Avalanche Current                    | 20                    | A    |
| EAS <sup>5</sup>                  | Avalanche energy                     | 460                   | mJ   |
| PD                                | Maximum Power Dissipation            | T <sub>C</sub> =25°C  | 173  |
|                                   |                                      | T <sub>C</sub> =100°C | 100  |
| T <sub>J</sub> , T <sub>STG</sub> | Junction & Storage Temperature Range | -55~175               | °C   |

### Thermal Characteristics

| Symbol           | Parameter                              | Typical | Unit |
|------------------|--|---------|------|
| Rθ <sub>jc</sub> | Thermal Resistance-Junction to Case    | 0.72    | °C/W |
| Rθ <sub>ja</sub> | Thermal Resistance-Junction to Ambient | 62.5    |      |

**Electrical Characteristics** (TA=25°C unless otherwise noted)

| Symbol   | Parameter                        | Test Conditions  | Min. | Typ  | Max. | Unit |
|--|----------------------------------|--|------|------|------|------|
| <b>Static Characteristics</b>                  |                                  |  |      |      |      |      |
| BV <sub>DSS</sub>                              | Drain-Source Breakdown Voltage   | V <sub>GS</sub> =0V, I <sub>D</sub> =250uA   | 80   | —    | —    | V    |
| I <sub>DSS</sub>                               | Zero Gate Voltage Drain Current  | V <sub>DS</sub> =85V, V <sub>GS</sub> =0V  | —    | —    | 1    | uA   |
|  |                                  | T <sub>J</sub> =125°C  | —    | —    | 100  |      |
| V <sub>GS(th)</sub>                            | Gate Threshold Voltage           | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA                               | 2    | 3    | 4    | V    |
| I <sub>GSS</sub>                               | Gate Leakage Current             | V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V   | —    | —    | ±100 | nA   |
| R <sub>DS(on)</sub> <sup>1</sup>               | Drain-Source On-Resistance       | V <sub>GS</sub> =10V, I <sub>D</sub> =50A  | —    | 6.6  | 8.5  | mΩ   |
|  |                                  |  | —    | —    | —    |      |
| <b>Diode Characteristics</b>                   |                                  |  |      |      |      |      |
| V <sub>SD</sub> <sup>1</sup>                   | Diode Forward Voltage            | I <sub>SD</sub> =50A, V <sub>GS</sub> =0V  | —    | —    | 1.2  | V    |
| I <sub>S</sub> <sup>3</sup>                    | Diode Continuous Forward Current |  | —    | —    | 100  | A    |
| t <sub>rr</sub>                                | Reverse Recovery Time            | I <sub>F</sub> =50A,   | —    | 44   | —    | nS   |
| Q <sub>rr</sub>                                | Reverse Recovery Charge          | di/dt=100A/us  | —    | 78.8 | —    | nC   |
| <b>Dynamic Characteristics<sup>2</sup></b>     |                                  |  |      |      |      |      |
| R <sub>G</sub>                                 | Gate Resistance                  | V <sub>GS</sub> =0V, V <sub>DS</sub> =0V,<br>Frequency=1MHz                            | —    | 1.3  | —    | Ω    |
| C <sub>iss</sub>                               | Input Capacitance                | V <sub>GS</sub> =0V, V <sub>DS</sub> =25V<br>Frequency=1MHz                            | —    | 3564 | —    | pF   |
| C <sub>oss</sub>                               | Output Capacitance               |  | —    | 408  | —    |      |
| C <sub>rss</sub>                               | Reverse Transfer Capacitance     |  | —    | 237  | —    |      |
| t <sub>d(on)</sub>                             | Turn-On Delay Time               | V <sub>DD</sub> =40V, I <sub>D</sub> =50A,<br>V <sub>GS</sub> =10V, R <sub>G</sub> =5Ω | —    | 32.3 | —    | nS   |
| t <sub>r</sub>                                 | Rise Time                        |  | —    | 22.7 | —    |      |
| t <sub>d(off)</sub>                            | Turn-Off Delay Time              |  | —    | 55.5 | —    |      |
| t <sub>f</sub>                                 | Fall Time                        |  | —    | 13.9 | —    |      |
| <b>Gate Charge Characteristics<sup>2</sup></b> |                                  |  |      |      |      |      |
| Q <sub>g</sub>                                 | Total Gate Charge                | V <sub>DS</sub> =64V, V <sub>GS</sub> =10V<br>I <sub>D</sub> =50A                      | —    | 60   | —    | nC   |
| Q <sub>gs</sub>                                | Gate-to-Source Charge            |  | —    | 17.6 | —    |      |
| Q <sub>gd</sub>                                | Gate-to-Drain Charge             |  | —    | 21   | —    |      |

Note: 1: Pulse test; pulse width ≤ 300us, duty cycle ≤ 2%.

2: Guaranteed by design, not subject to production testing.

3: Package limitation current is 50A. Calculated continuous current based on maximum allowable junction temperature.

4: Repetitive rating, pulse width limited by max junction temperature.

5: Starting T<sub>J</sub> = 25°C, L = 1mH, I<sub>AS</sub> = 40A.

Typical Characteristics




Figure 1 Maximum Forward Bias Safe Operating Area




Figure 2 Maximum Power Dissipation vs Case Temperature




Figure 3 Maximum Continuous Drain Current vs Case Temperature




Figure 4 Typical Output Characteristics




Figure 5 Drain-to-Source On Resistance vs Drain Current




Figure 6 Typical Transfer Characteristics

Typical Characteristics (Continued)




Figure 7 Typical Gate Charge vs Gate to Source Voltage




Figure 8 Typical Body Diode Transfer Characteristics




Figure 9 Typical Capacitance vs Drain to Source Voltage




Figure 10 Typical Drain to Source on Resistance vs Junction Temperature

Typical Characteristics (Continued)





Figure 11 Typical Theshold Voltage vs Junction Temperature

Figure 12 Typical Breakdown Voltage vs Junction Temperature





Figure 13 Maximum Effective Transient Thermal Impedance, Junction-to-Case

**Package Dimension**

TO-263

Unit: mm



单位: mm

| Symbol | Dimensions In Millimeters |       | Symbol | Dimensions In Millimeters |       |
|--------|---------------------------|-------|--------|---------------------------|-------|
|        | Min                       | Max   |        | Min                       | Max   |
| A      | 4.30                      | 4.70  | E      | 9.00                      | 9.40  |
| B      | 1.00                      | 1.40  | e1     | 2.34                      | 2.74  |
| b      | 0.70                      | 0.90  | e2     | 4.88                      | 5.28  |
| b1     | 1.15                      | 1.35  | L1     | 15.00                     | 16.00 |
| b2     | 0.40                      | 0.60  | L2     | 2.24                      | 2.84  |
| C      | 1.20                      | 1.40  | L3     | 1.20                      | 1.60  |
| D      | 9.80                      | 10.20 |        |                           |       |