

SOP8 Plastic-Encapsulate MOSFET

60V P-Channel MOSFET

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
-60V	75mΩ@-10V	-3A
	90mΩ@-4.5V	



Feature

- TrenchFET Power MOSFET
- Excellent $R_{DS(on)}$ and Low Gate Charge

Application

- Power switching application
- Hard switched and high frequency circuits
- DC-DC Converter

MARKING:



ABSOLUTE MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	I_D	-3	A
Plused Drain Current	I_{DM}	-12	A
Power Dissipation	P_D	1.4	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	89	$^{\circ}\text{C/W}$
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55~ +150	$^{\circ}\text{C}$







Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	-60			V
Zero gate voltage drain current	I_{DSS}	$V_{DS} = -48V, V_{GS} = 0V$			-1	μA
Gate-body leakage current	I_{GSS}	$V_{GS} = \pm 20V, V_{DS} = 0V$			± 100	nA
On characteristics⁽¹⁾						
Gate threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	-1.0	-1.7	-2.5	V
Drain-source on-resistance	$R_{DS(on)}$	$V_{GS} = -10V, I_D = -3A$		75	98	m Ω
		$V_{GS} = -4.5V, I_D = -1.6A$		90	120	
Forward transconductance	g_{FS}	$V_{DS} = -15V, I_D = -3A$	3			S
Switching characteristics⁽²⁾						
Input Capacitance	C_{iss}	$V_{DS} = -30V, V_{GS} = 0V, F = 1.0MHz$		1255		pF
Output Capacitance	C_{oss}			260		
Reverse Transfer Capacitance	C_{rss}			90		
Total gate charge	Q_g	$V_{DS} = -30V, V_{GS} = -10V, I_D = -3A$		34		nC
Gate-source charge	Q_{gs}			6		
Gate-drain charge	Q_{gd}			15		
Turn-on delay time	$t_{d(on)}$	$V_{DD} = -30V, I_D = -1A, V_{GS} = -10V, R_G = 6\Omega, R_L = 15\Omega$		16		ns
Turn-on rise time	t_r			19		
Turn-off delay time	$t_{d(off)}$			60		
Turn-off fall time	t_f			30		
Drain-Source Diode characteristics						
Diode Forward voltage ⁽¹⁾	V_{SD}	$V_{GS} = 0V, I_S = -3A$			1.2	V
Continuous drain-source current	I_S				3	A
Pulsed drain-source current	I_{SM}				12	A


Notes:

1. Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
2. Guaranteed by design, not subject to production testing.

Typical Characteristics



SOP8 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.156	0.250	0.006	0.010
D	4.700	5.100	0.185	0.201
e	1.270(BSC)		0.050(BSC)	
E	5.800	6.200	0.228	0.244
E1	3.700	4.100	0.146	0.161
L	0.400	1.270	0.016	0.05
θ	0°	8°	0°	8°

NOTICE

JSHD reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSHD does not assume any liability arising out of the application or use of any product described herein.